

US010180721B2

(12) United States Patent Hoen et al.

(54) FABRIC-BASED DEVICES WITH FORCE

(71) Applicant: Apple Inc., Cupertino, CA (US)

(72) Inventors: Storrs T. Hoen, Brisbane, CA (US);

Daniel D. Sunshine, Sunnyvale, CA (US); **Aidan N. Zimmerman**, Sunnyvale, CA (US); **Daniel A.**

Podhajny, San Jose, CA (US); Maurice

P. May, Sunnyvale, CA (US)

(73) Assignee: Apple Inc., Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/940,876

SENSING

(22) Filed: Mar. 29, 2018

(65) Prior Publication Data

US 2018/0364804 A1 Dec. 20, 2018

Related U.S. Application Data

- (60) Provisional application No. 62/519,564, filed on Jun. 14, 2017.
- (51) **Int. Cl. G06F 3/01** (2006.01) **A61B 5/00** (2006.01)
 (Continued)

(Continued)

(58) Field of Classification Search

CPC combination set(s) only.

See application file for complete search history.

(10) Patent No.: US 10,180,721 B2

(45) **Date of Patent: Jan. 15, 2019**

(56) References Cited

U.S. PATENT DOCUMENTS

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2443208 A 4/2008 WO 2017031153 A1 2/2017

OTHER PUBLICATIONS

BodiTrak "Smart Fabrics: For Intelligent and Interactive Products" Vista Medical, PatienTech, Apr. 2013. www.boditrak.com/pdf/ Industrial%20BT%20singles%20SCREEN%204-25-2013.pdf>.

Primary Examiner — Lisa Lea Edmonds (74) Attorney, Agent, or Firm — Treyz Law Group, P.C.; G. Victor Treyz

(57) ABSTRACT

A fabric-based item such as a fabric glove may include force sensing circuitry. The force sensing circuitry may include force sensor elements formed from electrodes on a compressible substrate such as an elastomeric polymer substrate. The fabric may include intertwined strands of material including conductive strands. Signals from the force sensing circuitry may be conveyed to control circuitry in the item using the conductive strands. Wireless circuitry in the fabricbased item may be used to convey force sensor information to external equipment. The compressible substrate may have opposing upper and lower surfaces. Electrodes for the force sensor elements may be formed on the upper and lower surfaces. Stiffeners may overlap the electrodes to help decouple adjacent force sensor elements from each other. Integrated circuits can be attached to respective force sensing elements using adhesive.

29 Claims, 17 Drawing Sheets

